

SAFETY DATA SHEET

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

As of the revision date above, this (M)SDS meets the regulations in the United Kingdom & Ireland.

PRODUCT

Product Name: ESSO UNLEADED
Product Description: Hydrocarbons and Additives
Product Code: 708001-60
Intended Use: Fuel

COMPANY IDENTIFICATION

Supplier: Esso Petroleum Company, Limited
ExxonMobil House
Ermyn Way
KT22 8UX Leatherhead, Surrey
United Kingdom

24 Hour Environmental / Health Emergency Telephone e-mail 01372 222 000 (UK) / +44 1372 222 000 (Ireland)
SDS-UK@EXXONMOBIL.COM

SECTION 2

HAZARDS IDENTIFICATION

This material is dangerous according to regulatory guidelines (see (M)SDS Section 15).

CLASSIFICATION: | F+; R12 | Carc. Cat. 2; R45 | Mut. Cat. 2; R46 | Repro. Cat. 3; R63 | Xn; R65 | Xi; R38 | R67 | N; R51/53 |

PHYSICAL / CHEMICAL HAZARDS

Extremely flammable. Material can release vapours that readily form flammable mixtures. Vapour accumulation could flash and/or explode if ignited. Material can accumulate static charges which may cause an incendiary electrical discharge.

HEALTH HAZARDS

May cause cancer. May cause heritable genetic damage. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Irritating to skin. Vapours may cause drowsiness and dizziness. May be irritating to the eyes, nose, throat, and lungs. May cause central nervous system depression. High-pressure injection under skin may cause serious damage. Prolonged and repeated exposure to benzene may cause serious injury to blood forming organs and is associated with anaemia and to the later development of acute myelogenous leukaemia (AML).

ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Note: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 2 of 12

SECTION 3	COMPOSITION / INFORMATION ON INGREDIENTS
------------------	---

This material is regulated as a preparation.

Reportable Hazardous Substance(s) or Complex Substance(s)

Name	CAS#	EINECS / ELINCS	Concentration *	Symbols/Risk Phrases
LOW BOILING POINT NAPHTHA	86290-81-5	289-220-8	> 99%	F+;R12, Xi;R38, T;Carc. Cat. 2;R45, T;Mut. Cat. 2;R46, Xn;Repro. Cat. 3;R63, Xn;R65, R67, N;R51/53, Note H

Reportable Hazardous Constituent(s) Contained in Complex Substance(s)

Name	CAS#	EINECS / ELINCS	Concentration *	Symbols/Risk Phrases
Benzene	71-43-2	200-753-7	0.1 - 1.0%	F;R11, Xi;R36/38, T;Carc. Cat. 1;R45, T;Mut. Cat. 2;R46, T;R48/23/24/25, Xn;R65, Note E
Toluene	108-88-3	203-625-9	> 5.0%	F;R11, Xi;R38, Xn;R48/20, Xn;Repro. Cat. 3;R63, Xn;R65, R67

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Note: Oxygenates may be present up to the maximum permitted by European Standard EN228.

SECTION 4	FIRST AID MEASURES
------------------	---------------------------

INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

SKIN CONTACT

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 3 of 12

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

Seek immediate medical attention. Do not induce vomiting.

NOTE TO PHYSICIAN

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

PRE-EXISTING MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY EXPOSURE

Benzene- Individuals with liver disease may be more susceptible to toxic effects.

SECTION 5	FIRE FIGHTING MEASURES
------------------	-------------------------------

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight streams of water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. If a leak or spill has not ignited, use water spray to disperse the vapours and to protect personnel attempting to stop a leak. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Unusual Fire Hazards: EXTREMELY FLAMMABLE. Vapour is flammable and heavier than air. Vapour may travel across the ground and reach remote ignition sources, causing a flashback fire danger. Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

Hazardous Combustion Products: Aldehydes, Smoke, Fume, Incomplete combustion products, Oxides of carbon, Sulphur Oxides

FLAMMABILITY PROPERTIES

Flash Point [Method]: <-35C (-31F) [IP 170/70]

Flammable Limits (Approximate volume % in air): LEL: 1.4 UEL: 7.6

Autoignition Temperature: >250°C (482°F)

SECTION 6	ACCIDENTAL RELEASE MEASURES
------------------	------------------------------------

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for Personal Protective Equipment.

SPILL MANAGEMENT

Land Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if

Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 4 of 12

you can do so without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. A vapour-suppressing foam may be used to reduce vapour. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Large Spills: Water spray may reduce vapour, but may not prevent ignition in enclosed spaces. Recover by pumping or with suitable absorbent.

Water Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Do not confine in area of spill. Advise occupants and shipping in downwind areas of fire and explosion hazard and warn them to stay clear. Allow liquid to evaporate from the surface. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Large Spills: Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7

HANDLING AND STORAGE

HANDLING

Avoid breathing mists or vapour. Avoid contact with skin. Use non-sparking tools and explosion-proof equipment. Potentially toxic/irritating fumes/vapour may be evolved from heated or agitated material. Do not siphon by mouth. Use only with adequate ventilation. Use proper bonding and/or earthing procedures. Do not use as a cleaning solvent or other non-motor fuel uses. For use as a motor fuel only. It is dangerous and/or unlawful to put petrol into unapproved containers. Do not fill container while it is in or on a vehicle. Static electricity may ignite vapour and cause fire. Place container on ground when filling and keep nozzle in contact with container. Do not use electronic devices (including but not limited to cellular phones, computers, calculators, pagers or other electronic devices etc) in or around any fuelling operation or storage area unless the devices are certified intrinsically safe by an approved national testing agency and to the safety standards required by national and/or local laws and regulations. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source).

Static Accumulator: This material is a static accumulator.

STORAGE

Ample fire water supply should be available. A fixed sprinkler/deluge system is recommended. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Outside or detached storage preferred. Storage containers should be earthed and bonded. Drums must be earthed and bonded and equipped with self-closing valves, pressure vacuum bungs and flame arresters.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 5 of 12

Substance Name	Form	Limit/Standard			Note	Source	Year
Benzene		TWA	1 ppm		Skin	UK EH40	2005
Benzene		TWA	3.25 mg/m3	1 ppm	Skin	EU. Dir. 04/37/EC Annex III A	2004
Benzene		STEL	2.5 ppm		Skin	ACGIH	2007
Benzene		TWA	0.5 ppm		Skin	ACGIH	2007
Gasoline	Vapour.	TWA	300 mg/m3	100 ppm		ExxonMobil	2007
LOW BOILING POINT NAPHTHA		STEL	500 ppm			ACGIH	2007
LOW BOILING POINT NAPHTHA		TWA	300 ppm			ACGIH	2007
Toluene		STEL	574 mg/m3	150 ppm	Skin	UK EH40	2005
Toluene		TWA	191 mg/m3	50 ppm	Skin	UK EH40	2005

Note: Information about recommended monitoring procedures can be obtained from the relevant agency(ies)/institute(s):

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Use explosion-proof ventilation equipment to stay below exposure limits.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No special requirements under ordinary conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

If prolonged or repeated contact is likely, chemical-resistant gloves are recommended. If contact with forearm is likely, wear gauntlet-style gloves. Nitrile, CEN standards EN 420 and EN 374 provide general requirements and lists of glove types.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 6 of 12

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

See Sections 6, 7, 12, 13.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Typical physical and chemical properties are given below. Consult the Supplier in Section 1 for additional data.

GENERAL INFORMATION

Physical State: Liquid

Colour: Pale yellow

Odour: Characteristic

Odour Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 C): 0.75

Flash Point [Method]: <-35C (-31F) [IP 170/70]

Flammable Limits (Approximate volume % in air): LEL: 1.4 UEL: 7.6

Autoignition Temperature: >250°C (482°F)

Boiling Point / Range: 28C (82F) - 210C (410F)

Vapour Density (Air = 1): 3 at 101 kPa

Vapour Pressure: < 11.97 kPa (89.78 mm Hg) at 20°C

Evaporation Rate (N-Butyl Acetate = 1): N/D

pH: N/A

Log Pow (n-Octanol/Water Partition Coefficient): > 1

Solubility in Water: Negligible

Viscosity: <1 cSt (1 mm²/sec) at 40°C

Oxidising properties: See Sections 3, 15, 16.

OTHER INFORMATION

Freezing Point: N/D

Melting Point: N/A

SECTION 10

STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Heat, sparks, flame, and build up of static electricity.

MATERIALS TO AVOID: Halogens, Strong Acids, Strong oxidisers, Alkalies

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 7 of 12

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11	TOXICOLOGICAL INFORMATION
-------------------	----------------------------------

Acute Toxicity

<u>Route of Exposure</u>	<u>Conclusion / Remarks</u>
INHALATION	
Toxicity: LC50 > 5000 mg/m3	Minimally Toxic. Based on test data for structurally similar materials.
Irritation: No end point data.	Elevated temperatures or mechanical action may form vapours, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs. Based on assessment of the components.
INGESTION	
Toxicity: LD50 > 2000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials.
Skin	
Toxicity: LD50 > 2000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials.
Irritation: No end point data.	Moderately irritating to skin with prolonged exposure. Based on test data for structurally similar materials.
Eye	
Irritation: Data available.	May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials.

CHRONIC/OTHER EFFECTS

For the product itself:

Laboratory animal studies have shown that prolonged and repeated inhalation exposure to light hydrocarbon vapours in the same boiling range as this product can produce adverse kidney effects in male rats. However, these effects were not observed in similar studies with female rats, male and female mice, or in limited studies with other animal species. Additionally, in a number of human studies, there was no clinical evidence of such effects at normal occupational levels. In 1991, The U.S. EPA determined that the male rat kidney is not useful for assessing human risk. Vapour concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Gasoline unleaded: Carcinogenic in animal tests. Chronic inhalation studies resulted in liver tumours in female mice and kidney tumours in male rats. Neither result considered significant for human health risk assessment by the United States EPA and others. Did not cause mutations in-vitro or in-vivo. Negative in inhalation developmental studies and reproductive tox studies. Inhalation of high concentrations in animals resulted in reversible central nervous system depression, but no persistent toxic effect on the nervous system. Non-sensitizing in test animals. Caused nerve damage in humans from abusive use (sniffing).

Contains:

BENZENE: Caused cancer (leukemia), damage to the blood-producing system, and serious blood disorders from prolonged, high exposure based on human epidemiology studies. Caused genetic effects and effects on the immune system in laboratory animal and some human studies. Caused toxicity to the fetus in laboratory animal studies. **TOLUENE :** Concentrated, prolonged or deliberate inhalation may cause brain and nervous system damage. Prolonged and repeated exposure of pregnant animals (> 1500 ppm) have been reported to cause adverse fetal developmental effects.

Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 8 of 12

Additional information is available by request.

SECTION 12	ECOLOGICAL INFORMATION
-------------------	-------------------------------

The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

MOBILITY

More volatile component -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

Less volatile component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Majority of components -- Expected to be inherently biodegradable

Atmospheric Oxidation:

More volatile component -- Expected to degrade rapidly in air

BIOACCUMULATION POTENTIAL

Majority of components -- Potential to bioaccumulate is low.

OTHER ECOLOGICAL INFORMATION

VOC: 100 %wt

SECTION 13	DISPOSAL CONSIDERATIONS
-------------------	--------------------------------

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

REGULATORY DISPOSAL INFORMATION

European Waste Code: 13 07 02

NOTE: These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code(s).

This material is considered as hazardous waste pursuant to Directive 91/689/EEC on hazardous waste, and subject to the provisions of that Directive unless Article 1(5) of that Directive applies.

Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 9 of 12

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14

TRANSPORT INFORMATION

LAND (ADR/RID)

Proper Shipping Name: MOTOR SPIRIT or GASOLINE or PETROL

Hazard Class: 3

Classification Code: F1

UN Number: 1203

Packing Group: II

Label(s) / Mark(s): 3

Hazard ID Number: 33

CEFIC Tremcard: 30S1203

Hazchem EAC: 3YE

Transport Document Name: UN1203, MOTOR SPIRIT or GASOLINE or PETROL, 3, PG II

INLAND WATERWAYS (ADNR)

Proper Shipping Name: MOTOR SPIRIT or GASOLINE or PETROL

Hazard Class: 3

Hazard ID Number: 33

UN or ID Number: 1203

Packing Group: II

Label(s) / Mark(s): 3

Transport Document Name: UN1203, MOTOR SPIRIT or GASOLINE or PETROL, 3, PG II

SEA (IMDG)

Proper Shipping Name: MOTOR SPIRIT or GASOLINE or PETROL

Hazard Class & Division: 3

UN Number: 1203

Packing Group: II

Label(s): 3

EMS Number: F-E, S-E

Transport Document Name: MOTOR SPIRIT or GASOLINE or PETROL, 3, UN1203, PG II, (-35°C c.c.)

AIR (IATA)

Proper Shipping Name: Gasoline

Hazard Class & Division: 3

UN Number: 1203

Packing Group: II

Label(s): 3

Transport Document Name: GASOLINE, 3, UN1203, PG II

SECTION 15

REGULATORY INFORMATION

Material is dangerous as defined by the EU Dangerous Substances/Preparations Directives.

Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 10 of 12

CLASSIFICATION: Extremely flammable. Category 2 Carcinogen. Category 2 Mutagen. Category 3 Toxic to reproduction. Harmful. Irritant. Dangerous for the environment.

EU LABELING:

Symbol: F+, T, N



Extremely flammable.



Dangerous for the environment.

Nature of Special Risk: R12; Extremely flammable. R45; May cause cancer. R46; May cause heritable genetic damage. R63; Possible risk of harm to the unborn child. R65; Harmful: may cause lung damage if swallowed. R38; Irritating to skin. R67; Vapours may cause drowsiness and dizziness. R51/53; Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Advice: S2; Keep out of the reach of children. S16; Keep away from sources of ignition - No smoking. S23; Do not breathe vapour. S24; Avoid contact with skin. S29; Do not empty into drains. S43; In case of fire use carbon dioxide (CO₂), foam, dry chemical, or water fog. S45; In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S53; Avoid exposure - obtain special instructions before use. S61; Avoid release to the environment. Refer to special instructions/safety data sheets. S62; If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Contains: Petroleum Naphtha

REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

Complies with the following national/regional chemical inventory requirements: PICCS, EINECS, DSL, KECI

Applicable EU Directives and Regulations:

EU Directive:

76/769/EEC [...marketing and use of certain dangerous substances and preparations and amendments thereto]

92/85/EEC [...pregnant workers...recently given birth or...breastfeeding directive]

1999/13/EC [...on the limitation of emissions of volatile organic compounds... directive and amendments thereto]

94/33/EC [...on the protection of young people at work]

This product is impacted by the classification and/or labelling changes introduced by the 29th Adaptation to Technical Progress of the EU Dangerous Substances Directive (67/548/EEC). The SDS may have been updated in the following sections 2, 3, 11, and 15 where appropriate.

SECTION 16

OTHER INFORMATION

N/D = Not determined, N/A = Not applicable

KEY TO THE RISK CODES CONTAINED IN SECTION 2 AND 3 OF THIS DOCUMENT (for information only):

R11; Highly flammable.

Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 11 of 12

R12; Extremely flammable.
R36; Irritating to eyes.
R38; Irritating to skin.
R45; May cause cancer.
R46; May cause heritable genetic damage.
R48/20; Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R48/23; Toxic: danger of serious damage to health by prolonged exposure through inhalation.
R48/24; Toxic: danger of serious damage to health by prolonged exposure in contact with skin.
R48/25; Toxic: danger of serious damage to health by prolonged exposure if swallowed.
R51/53; Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63; Possible risk of harm to the unborn child.
R65; Harmful: may cause lung damage if swallowed.
R67; Vapours may cause drowsiness and dizziness.

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Revision Changes:

Section 06: Protective Measures was modified.
Section 13: Empty Container Warning was modified.
Section 09: Phys/Chem Properties Note was modified.
Section 09: Color was modified.
Section 11: Ingestion Lethality Conclusion was modified.
Section 09: Boiling Point °C(°F) was modified.
Section 08: Hand Protection was modified.
Section 08: Environmental Control - Note was modified.
Section 09: Vapour Pressure was modified.
Section 07: Handling and Storage - Handling was modified.
Section 06: Accidental Release - Spill Management - Water was modified.
Section 09: Relative Density - Header was modified.
Section 09: Flash Point °C(°F) was modified.
Section 09: Viscosity was modified.
Hazard Identification: Classification was modified.
Section 15: National Chemical Inventory Listing was modified.
Section 11: Other Health Effects was modified.
Section 08: Exposure Limits Table was modified.
Section 11: Inhalation Lethality Test Data was modified.
Section 01: Company Contact Methods Sorted by Priority was modified.
Section 08: Environmental Control - Note was deleted.

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.



Product Name: ESSO UNLEADED

Revision Date: 14Dec2007

Page 12 of 12

Internal Use Only

MHC: 1A, 0, 0, 0, 3, 1

PPEC: CF

DGN: 7055326XGB (555769)
