



Diesel UK Marketing Specification

Component Name	Units	Min	Max	Method
Appearance (@ 15 °C)		C&B, Free from Visible Sediment & Water		Visual
Ash Content	%		0.010	EN ISO 6245
Carbon Residue on 10% dist residue ⁴	%		0.3	EN ISO 10370
Cetane Index		46		EN ISO 4264
Cetane Number		51		EN ISO 15195
Cloud (Aim)	°C		+3 (S) -5 (W)	EN 23015 / ISO 3015
Cold Filter Plugging Point	°C		-5 (S) -15 (W)	EN 116
Copper Corrosion	3hr @ 50 °C		Class 1	EN ISO 2160
Density	kg/l @ 15 °C	0.8200	0.8450	EN ISO 12185
% Recovered @ 250 °C	Vol %		<65.0	EN ISO 3405
% Recovered @ 350 °C	Vol %	80		
95% Recovered @	°C		360.0	
Fatty Acid Methyl Ester (FAME) Content	%		7.0	EN 14078
Filter Blocking Tendency			2.52 (W)	IP 387 Proc B
Flash Point	°C	> 55.0		EN ISO 2719
Lubricity, corrected WSD @ 60 °C	µm		460.0	EN ISO 12156-1
Manganese Content	mg/l		2.0	EN 16135
Odour		Merchantable		
Oxidation Stability	g/m ³		25.0	EN ISO 12205
Oxidation Stability	hours	20		EN 15751
Polycyclic Aromatics Hydrocarbons	% (m/m)		8.0	EN ISO 12916
Sulphur	mg/kg		10.0	EN ISO 20846
Total Contamination	mg/kg		24.0	EN 12662
Visco @ 40c	mm ² /s	2	4.5	EN ISO 3104
Water	mg/kg		200.0	EN ISO 12937

Notes:

- Unless otherwise advised the following seasonal dates apply at point of sale :
 Sumer: 16 March - 15 November (incl)
 Winter: 16 November - 15 March (incl)
- Latest test methods or technical equivalents used
- May contain a multifunctional diesel additive Package
- May contain ignition improver in which case the MCR test is not valid
- FAME shall meet the requirements of EN 14214
- This product shall always meet **BS EN590 2013 + A1: 2017 Specification (Diesel)**
- This document is accurate at the date of issue and supersedes all previous issues

Ver: 1.11 - JE
 Pub: Dec 12 2017